

CONTACT ARRANGEMENT

CROSS REFERENCE TO RELATED APPLICATIONS

This application is the US national phase of PCT application PCT/EP2005/007209, filed 5 July 2005, published 2 March 2006 as WO 2006/021260, and claiming the priority of German patent application 102004041317.7 itself filed 28 August 2004, whose entire disclosures are herewith incorporated by reference.

FIELD OF THE INVENTION

The invention relates to a contact arrangement with a fixed electrical contact, ~~which~~ that is fastened to an insulating rod, for a step switch or tap changer.

BACKGROUND OF THE INVENTION

Step switches and tap changers are known ~~apparatus~~ for switching ~~[[over]]~~ between different winding taps of a regulating transformer for voltage regulation. They have stationary contacts ~~which~~ that are electrically connected with the individual winding taps of a regulating transformer and are usually arranged in phases on circular tracks disposed one above the other. In each horizontal plane electrical connection can be made with the stationary contacts by a movable contact, usually a contact bridge, connected with the electrical load shunt. The stationary contacts are in that case fastened to vertically extending insulating rods of hard paper or glass-fiber-reinforced synthetic material or also in the wall of insulating cylinders.

The fastening to insulating rods is hitherto usually carried out in that not only the corresponding insulating rod itself, but also a fastening part of the stationary contact are provided with respective bores and this contact arrangement is tightened together by screws and nuts. Such a contact arrangement with a screw connection is known from FIG. 1 of AT-PS 187991. However, the disadvantage of this fastening, which is simple in itself, consists in that due to the metallic fastening means penetrating the insulating rods the voltage resistance of the entire step switch or tap changer is impaired.

Numerous proposals have already become known for remedying this problem. The mentioned AT-PS 187991 itself describes a further contact arrangement in which clamping members are provided, ~~which~~ that embrace the respective insulating rods and ~~[[which]]~~ that are screw-connected outside these insulating rods, so that no metallic fastening means penetrate the insulating rods themselves. A quite similar solution was subsequently proposed once again in AT-PS 315302. Bores through the insulating rods can indeed be avoided by that, but metallic fastening means - even if outside the insulating rods - are still present; the disadvantageous influence thereof on the voltage resistance thus continues to be present.

A further contact arrangement is known from AT-PS 382476, wherein a sleeve is provided at the contact to be fastened, the sleeve having on one side a collar with a diameter greater than the bore diameter of the respective insulating rod. On the other side

of the insulating rod the sleeve of the contact to be fastened has an annular groove in which a slotted ring of plastics material is placed. However, this arrangement has not been able to gain acceptance in practice. Insulating material rods usually shrink during the necessary drying of the respective step switch or tap changer prior to being placed in operation; in the case of this known contact arrangement the individual contacts then loosen due to the fastening purely by shape-locking coupling, which is not desirable.

A contact arrangement as well as an associated fastening method are known from DE-PS 3801151 and 3801152, wherein the contact is held by permanent deformation of its shank sleeve on the outer side, stated more precisely by expansion of bores specifically provided for that purpose. This is relatively costly and requires a special tool for expanding the described bores and beyond that similarly enables only fastening in a shape-locking manner. Finally, disassembly of this contact arrangement without destruction is also not possible.

DE-GM 9010730 proposes a similar contact arrangement; in this case the shank sleeve of the contact is weakened in its cross-section in a defined region and a bulge-like thickening of the shank sleeve is achieved at this location by upsetting from the outside, whereby fixing is effected. A special tool is indeed not required for the described upsetting from outside - a hammer suffices - but here, too, there is the disadvantage that, apart from the connection which is again only a shape-locking coupling,

disassembly is similarly possible only by destruction of the contact.

DE-PS 4236528 (US 5,374,781) describes a further possibility of fastening a contact by a transverse pin, ~~which that~~ penetrates the contact ~~shank~~ sleeve, and locking means co-operating therewith. This connection is detachable without destruction, can also be executed to be force-locking and is additionally also suitable for simultaneous fastening of ~~screening~~ shield rings. Nevertheless, it was not able gain acceptance, because it is of relatively complicated construction and requires a multiplicity of individual parts produced with a high degree of accuracy relative to one another.

OBJECT OF THE INVENTION

It is accordingly the object of the invention to ~~indicate~~ provide a contact arrangement of the kind ~~stated in the~~ introduction described above in which a fixed electrical contact can be fastened to an insulating rod without impairment of the voltage strength taking place due to metallic fastening parts, wherein the contact arrangement moreover is of simple and economic construction, is secured against loosening of the fixed contact and, in addition, can be demounted again without destruction.

SUMMARY OF THE INVENTION

This object is fulfilled attained by a contact arrangement ~~with the features of the first patent claim. The~~ subclaims relate to particularly advantageous developments of the invention. ~~According to the invention the contact arrangement~~

~~of the kind stated in the introduction consists wherein~~, apart from the actual contact ~~which~~ that is to be fastened to an insulating rod, ~~additionally of there is also~~ a two-part contact holder of insulating material as well as pins, similarly of insulating material, for fastening. According to the invention the actual contact is of U-shaped construction. The contact arrangement according to the invention has a number of advantages: no metallic parts of any kind are required for fastening, the entire arrangements consists of only a few parts ~~[[which]]~~ that can be produced in simple manner and, nevertheless, a secure fastening is possible without special tools. The fastening according to the invention ensures, even in the case of possible shrinkage of the insulating rod or later vibrations in operation, a reliable, secure fastening; finally - again without a special tool - ~~demounting~~ removal in simple manner and without destruction is possible at any time.

According to an advantageous development of the invention additional ~~screening~~ shield caps, ~~which~~ that surround the contact at both longitudinal ends ~~sides in longitudinal direction~~ of the insulating rod, are fastenable therewith in simple manner.

BRIEF DESCRIPTION OF THE DRAWING

The invention will be explained in more detail in the following by way of example with reference to drawings, in which:

FIG. 1 shows a contact arrangement according to the invention in side illustration view,

FIG. 2 shows this contact arrangement rotated horizontally through 90° ,

FIG. 3 shows a section in the plane A-A of FIG. 1 through this contact arrangement,

5 FIG. 4 shows a section in the plane B-B of FIG. 2 through this contact arrangement,

FIG. 5 shows a section in the plane C-C of FIG. 1 through this contact arrangement,

10 FIG. 6 shows a perspective illustration view of the contact arrangement,

FIG. 7 shows a corresponding illustration view again turned horizontally through 90° ,

FIG. 8 shows a contact by itself, in perspective illustration view,

15 FIG. 9 shows this contact turned through 180° ,

FIG. 10 shows an upper contact holder by itself, in perspective illustration view,

FIG. 11 shows a lower contact holder by itself, in perspective illustration view,

20 FIG. 12 shows a pin for fastening,

FIG. 13 shows an upper ~~screening~~ shield ring by itself, in perspective illustration view, and

FIG. 14 shows a lower ~~screening~~ shield ring by itself, in perspective illustration view.

25 SPECIFIC DESCRIPTION

In FIGS. 1 to 7, which show the entire contact arrangement according to the invention ~~in mounted state~~ when installed, for reasons of clarity not all reference numerals are entered.

5 In FIGS. 1 to 7, which illustrate the entire contact arrangement, there is shown ~~at the outset~~ an insulating rod 1 to which the contact arrangement according to the invention is to be fastened. The individual parts of the contact arrangement according to the invention are illustrated separately in FIGS. 8 to
10 14.

The insulating rod 1 has for each contact arrangement ~~which that~~ is to be fastened to it a respective upper fastening bore 11 and a respective lower fastening bore 12. The contact 2, which is of U-shape ~~d-construction~~, is ~~arranged at~~ mounted on the
15 insulating rod 1. It has a bight forming a contact region 21 ~~that is the region in which~~ where electrical connection can be made at the top and bottom by a movable contact (not illustrated). It ~~additionally also~~ also has a long limb 22 and a short limb 23, a connecting bore 24 ~~[-]~~ with which the electrical connecting line
20 (not illustrated here) for the respective winding tap of the regulating transformer is connectable ~~[-]~~ being ~~disposed~~ formed in the long limb 22. The long limb 22 ~~additionally also~~ also has an upper part fastening bore 25 and a lower fastening bore 26. The short limb 23 extends on the opposite side of the insulating rod 1
25 parallel to the long limb 22 and similarly has an upper fastening bore 27 as well as a lower fastening bore 28. The fastening bores

25, 27 and 26, 28 correspond with the fastening bores 11 and 12
~~which penetrate~~ that extend through the insulating rod 1. At the
top, the contact 2 is fixed by an upper contact holder 3. The
contact holder 3 has a guide ~~shank~~ sleeve 31 ~~[[, the]]~~ whose
5 internal dimensions ~~of which~~ correspond with the external
dimensions of the insulating rod 1. ~~[[;]]~~ It is pushed onto this
insulating rod 1. It additionally also has an encircling collar
32, at which lateral, integrally formed contact mounts 33 and 34
disposed opposite one another are provided. In the mounted state
10 the upper region of the long limb 22 of the contact 2 rests in the
contact mount 33 and the upper region of the short limb 23
correspondingly rests in the contact mount 34. ~~counter-bearing~~
Seats 35, 36 ~~, which that~~ are similarly disposed opposite one
another, for a pin 5, which is explained still later, are provided
15 in the region of the contact mounts 33, 34. Finally, a bore 37 is
~~disposed~~ formed there and, on the opposite side, a further bore 38
through the guide ~~shank~~ sleeve 31.

From the bottom the contact 2 is surrounded in the
mounted state by a lower contact holder 4. The lower contact
20 holder 4 is constructed identically to the already described upper
contact holder 3. ~~[[;]]~~ It is pushed from below onto the contact
rod 1. It again has in entirely analogous manner a guide ~~shank~~
sleeve 41 ~~[[at]]~~ on which is integrally formed an encircling collar
42 ~~, which that~~ in turn has lateral integrally formed contact
25 mounts 43 and 44. The lower region of the long limb 22 rests in
the contact mount 43 and the lower region of the short limb 23

rests in the contact mount 44. ~~counter-bearing~~ Seats 45 and 46 and bores 47 and [-] opposite thereto, [-] 48 are again disposed in this region.

For fastening, ~~merely~~ only an upper pin 5 and a lower pin 6, both of insulating material, for example glass-fiber synthetic material are now required. The upper pin 5 is [[led]] fitted horizontally from outside through the upper fastening bore 25 of the long limb 22 of the contact 2, further through the bore 37 of the upper contact holder 3, on through the upper fastening bore 11 of the insulating rod 1, further through the bore 38 of the upper contact holder 3 on the opposite side and finally through the upper fastening bore 27 of the opposite short limb 23 of the contact 2 and then points outward [[ly]] again on the opposite side.

Correspondingly, the lower pin 6 is [[led]] fitted initially through the lower fastening bore 26 of the long limb 22 of the contact 2, further through the bore 47 of the lower contact holder 4, on through the lower fastening bore 12 of the insulating rod 1, then through the bore 48 on the opposite side of the lower contact holder 5 and finally through the lower fastening bore 28 in the short limb 23 of the contact 2, before it similarly goes out ~~wardly~~ again on the opposite side.

A reliable fastening of the contact 2 to the insulating rod 1 is thus [[given]] provided. Due to the contact holders 3 and 4 arranged at the top and the bottom on both sides, [-] the contact 2 is reliably fixed and [[firm]] solidly held under all operating conditions. The pins 5 and 6 ~~are dimensioned in their~~ have such

lengths ~~in such a manner~~ that they rest laterally on the corresponding ~~counter-bearing~~ seats 35, 36 for the upper pin 5 or ~~counter-bearing~~ seats 45, 46 for the lower pin 6.

According to an advantageous development of the invention
5 the outer regions of the ~~counter-bearing~~ seats 35, 36 are vertically ~~displaced~~ offset by a small amount relative to the upper fastening bore 11 and those of the ~~counter-bearing~~ seats 45, 46 relative to the lower fastening bore 12, so that, due to the limited resilience ~~— which is present within certain limits —~~ of
10 the components the introduced pins 5 and 6 are pressed during mounting ~~[[in]]~~ axially direction against the outer regions of the ~~counter-bearing~~ seats 35, 36 or 45, 46 until in the final mounting position these ~~counter-bearing~~ seats ~~[[']]~~ snap closed ~~[[']]~~ in their outer region and the respective pin is thereby axially
15 secured. This prevents unintended slipping out.

According to a development of the invention an upper screening shield cap 7 and a lower screening shield cap 8 are additionally also provided. The open sides of the screening shield caps 7 and 8 respectively face the respective contact member 2.
20 The upper screening shield cap 7 has a first fastening strap 71 and, opposite thereto, a second fastening strap 72 ~~[[;]]~~ formed with respective bores 73 and 74 ~~are disposed therein~~. The upper screening shield cap 7 is pushed from above onto the insulating rod 1 so that the fastening straps 71, 72 point downward ~~[[ly]]~~. In
25 entirely analogous manner the identically constructed screening shield cap 8 in the pushed-on state has an upwardly pointing first

fastening strap 81 and, opposite thereto, a second fastening strap 82 ~~[[,]]~~ formed with respective bores 83 and 84 ~~again being disposed therein~~. The fastening straps 71, 72 or 81, 82 as well as the bores 73, 74 or 83, 84 ~~disposed therein~~ are dimensioned in such a manner that the fastening pins 5 and 6 in the mounted state ~~[[are]]~~ also ~~[[led]]~~ extend through these bores, whereby the screening shield caps 7 and 8 in common with the contact 2 and upper contact holder 3 as well as lower contact holder 4 are fastened to the insulating rod 1 without additional fastening means being required. The electrical contact between the respective screening shield cap 7 or 8 and the contact 2 is achieved by means of the respective pre-bent fastening straps 71, 72 or 81, 72. Moreover, ~~[[the]]~~ side edges of the straps 71, 72 or 81, 82 ~~, which that~~ are guided in the pockets 39, 49 of the respective contact holder 3, 4 so as to be positively mechanically coupled in ~~mechanically positive manner, thereto~~ prevent lateral twisting.

In practice, the contact 2 is ~~, for mounting,~~ installed by being brought to the corresponding side of the insulating rod 1 to which it is to be fastened. Subsequently, the upper contact holder 3 is pushed onto the insulating rod 1 from above and the lower contact holder 4 from below. The two contact holders 3 and 4 fix the contact 2. Subsequently, the upper screening shield cap 7 can be pushed onto the insulating rod from above and the lower screening shield cap 8 from below.

The following bores are aligned in an upper horizontal plane in the setting provided for fixing:

Upper fastening bore 25 of the contact 2, bore 37 of the upper contact holder 3, bore 73 of the ~~screening~~ shield cap 7, upper fastening bore 11 of the insulating rod 1, bore 74 of the upper ~~screening~~ shield cap 7, bore 38 of the upper contact holder 3 and upper fastening bore 27 of the contact 2.

The upper pin 5 is horizontally pushed in through these aligned bores. In the pushed-in state the upper pin 5 rests laterally ~~[[by]]~~ at its free ends on the inner counter-bearing seat 35 or ~~[[-]]~~ on the other side ~~[[-]]~~ on the inner counter-bearing seat 36.

Correspondingly, the following bores are aligned in a lower horizontal setting:

Lower fastening bore 26 of the contact 2, bore 47 of the lower contact holder 4, bore 83 of the lower ~~screening~~ shield cap 8, lower fastening bore 12 of the insulating rod 1, bore 84 of the lower ~~screening~~ shield cap 8, bore 48 of the lower contact holder 4 and lower fastening bore 28 of the contact 2.

The lower pin 6 is pushed in horizontally through these aligned bores. In the pushed-in state the lower pin 6 rests laterally by its free ends on the inner counter-bearing seat 45 or ~~[[-]]~~ on the other side ~~[[-]]~~ on the inner counter-bearing seat 46.

Overall, the ~~explained~~ described contact arrangement according to the invention has, apart from the actual conductive contact 2, ~~which~~ that is fastened to the insulating rod 1, thus only three different further components:

a contact holder ~~, which that~~ can, for example, be produced economically as an injection-molded part from plastic ~~s material~~ and which ~~that~~ is pushed onto the insulating rod 1 not only as upper contact holder 3, but also ~~—turned when rotated~~ through 180 degrees ~~[[—]]~~ as an identical lower contact holder 4,

a screening shield cap, ~~which that~~ can easily be made from sheet metal and which ~~that~~ is pushed onto the insulating rod not only as upper screening shield cap 7, but also ~~—turned when rotated~~ through 180 degrees ~~[[—]]~~ as an identical lower screening shield cap 8, and

~~[[a]]~~ simple identical pins of insulating material, which ~~that~~ serve ~~s not only~~ as upper fastening pin 5, but also as lower fastening pin 6.

~~Reference Numeral List~~

- ~~1 — insulating rod~~
- ~~11 — upper fastening bore~~
- ~~12 — lower fastening bore~~
- ~~2 — contact~~
- ~~21 — contact region~~
- ~~22 — long limb~~
- ~~23 — short limb~~
- ~~24 — connecting bore in 22~~
- ~~25 — upper fastening bore in 22~~
- ~~26 — lower fastening bore in 22~~
- ~~27 — upper fastening bore in 23~~
- ~~28 — lower fastening bore in 23~~
- ~~3 — upper contact holder~~
- ~~31 — guide shank~~
- ~~32 — encircling~~
- ~~33 — integrally formed contact mount for 22~~
- ~~34 — integrally formed contact mount for 23~~
- ~~35 — counter-bearing~~
- ~~36 — counter-bearing~~

5
10
15
20
25

~~37 bore~~
~~38 bore~~
~~39 pocket~~
~~4 lower contact holder~~
~~41 guide shank~~
~~42 encircling~~
~~43 integrally formed contact mount for 22~~
~~44 integrally formed contact mount for 23~~
~~45 counter-bearing~~
~~46 counter-bearing~~
~~47 bore~~
~~10~~
~~48 bore~~
~~49 pocket~~
~~5 upper pin~~
~~6 lower pin~~
~~7 upper screening cap~~
~~71 fastening strap~~
~~72 fastening strap~~
~~73 bore~~
~~74 bore~~
~~7 lower screening cap~~
~~81 fastening strap~~
~~82 fastening strap~~
~~83 bore~~
~~84 bore~~